



DISAB TrailerVAC™ SET-10T

Usage

DISAB TrailerVAC™ SET-10T units are a series of mobile, electrical powered vacuum loaders that are fitted onto trailer chassis. Suitable for suctioning both dry and liquid materials for any industrial application. When connected to a fixed pipe system, these units can operate as a perfect central vacuum unit for industrial installations.

Typical users include manufacturers of cement, lime, gypsum, tiles, chemicals, steel mills, cleaning contractors and more.

Characteristics

DISAB TrailerVAC™ SET-10T is a great choice for industrial settings where cleaning needs to be done in multiple locations/buildings. The large hopper placed on a trailer for towing by a tractor or similar makes the whole unit easy to transport. The unit can start operating as soon as a hose/pipe is connected. Also, the handling of the dust is easily carried out as there is a built-in tipping cylinder for the discharge.

The rigid trailer can carry high load and together with high suction capacity using Roots pump, the unit is especially suited for heavy industrial environments.

Benefits

A DISAB TrailerVAC™ SET-10T unit is suitable for use in any industrial application where collection of dust is required i.e. to clean out; deep pits, trenches, bucket elevators, conveyor spills, overhead cranes and runways, dust collectors, processing machines etc. The unit is specially suitable where bulky or sticky material shall be collected due to its convenient discharging.

Other benefits include:

- Roots-type high vacuum pump.
- Filter system for dry and wet material.
- Automatic filter cleaning without compressed air.
- Electrical motor, 30 to 55 kW.
- Large dustbins with tailgate for easy discharge.
- Very low noise level due to well insulated motor compartment housing.
- The vacuum pump is equipped with a spring loaded safety valve regulating the vacuum not to exceed its maximum operating range.
- The filter system is equipped with a vacuum controlled ATM (air-repulse) filter cleaning system.
- ATEX approved models available.
- Range of flexible hoses and a specifically designed tool set for bulk collection.

Technical Data Chart for DISAB TrailerVAC™ SET-10T

Description

Vacuum pump	Three-Lobe Roots Pump	Max vacuum, mbar	500
Air volume m ³ /h (unloaded)	1,850 (30)	Electrical motor, kW	30
	2,245 (37)		37
	2,617 (45)		45
	3,360 (55)		55
Tank volume (m ³)*	3.5	Total Tank Volume (m ³)	5.5
Tank tipping system	Hydraulic cylinder, single acting system. Hydraulically operated and locked tailgate as add-on.	Noise Level dB(A) (at 1m/5 m distance)	65 (30)
Main filter system (m ²)	15		67 (37)
			70 (45)
ATEX approved	On request		71 (55)
		Safety filter surface (m ²)	18
		Voltage Frequency, V/Hz	400/50


* Excluding filter volume

Miscellaneous

Trailer	10 tonnes capacity	Filter Class	L, M IEC EN 60335-2-69
Hose Connection	Dia 152 mm or smaller	Material	Steel S 235 JG2
Painting	System C2, RAL 3003 red	Max Towing Speed	40 km/h

Weight and Dimensions

A x B x C x D (mm)	5,640 x 2,100 x 2,600 x 4,000
Weight, kg (approx)	4,450 (30)
	4,550 (37)
	4,900 (45)
	5,000 (55)



The DISAB TrailerVAC™ SET-10T is ideal for heavy industries that often have production, raw material handling and packaging scattered throughout several different buildings.

A DISAB TrailerVAC™ SET-10T meets the high demands from the industry due to its efficiency, reliability, ease of operation and maintenance giving excellent value for money.